

MBL800E33E

Silicon N-channel IGBT 3300V E version

FEATURES

- * Soft switching behavior & low conduction loss:
Soft low-injection punch-through High conductivity IGBT.
- * Low driving power due to low input capacitance MOS gate.
- * Low noise recovery: Ultra soft fast recovery diode.
- * High thermal fatigue durability: ($\Delta T_c=70K$, $N>30,000$ cycles)
AlSiC base-plate/AlN substrate

ABSOLUTE MAXIMUM RATINGS ($T_c=25^\circ\text{C}$)

Item	Symbol	Unit	MBL800E33E
Collector Emitter Voltage	V_{CES}	V	3,300
Gate Emitter Voltage	V_{GES}	V	± 20
Collector Current	DC	I_C	800
	1ms	I_{Cp}	1,600
Forward Current	DC	I_F	800
	1ms	I_{FM}	1,600
Junction Temperature	T_j	$^\circ\text{C}$	-40 ~ +125
Storage Temperature	T_{stg}	$^\circ\text{C}$	-40 ~ +125
Isolation Voltage	V_{ISO}	V_{RMS}	6,000(AC 1 minute)
Screw Torque	Terminals (M4/M8)	-	2/10 (1)
	Mounting (M6)	-	6 (2)

Notes: (1) Recommended Value $1.8\pm 0.2/9\pm 1\text{N}\cdot\text{m}$ (2) Recommended Value $5.5\pm 0.5\text{N}\cdot\text{m}$

ELECTRICAL CHARACTERISTICS

1) IGBT + FWD

Item	Symbol	Unit	Min.	Typ.	Max.	Test Conditions
Collector Emitter Cut-Off Current	I_{CES}	mA	-	-	12	$V_{CE}=3,300\text{V}$, $V_{GE}=0\text{V}$, $T_j=25^\circ\text{C}$
Gate Emitter Leakage Current	I_{GES}	nA	-500	-	+500	$V_{GE}=\pm 20\text{V}$, $V_{CE}=0\text{V}$, $T_j=25^\circ\text{C}$
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	V	3.0	3.5	4.2	$I_C=800\text{A}$, $V_{GE}=15\text{V}$, $T_j=125^\circ\text{C}$
Gate Emitter Threshold Voltage	$V_{GE(TH)}$	V	4.5	6.0	7.0	$V_{CE}=10\text{V}$, $I_C=800\text{mA}$, $T_j=25^\circ\text{C}$
Input Capacitance	C_{ies}	nF	-	70	-	$V_{CE}=10\text{V}$, $V_{GE}=0\text{V}$, $f=100\text{kHz}$, $T_j=25^\circ\text{C}$
Internal Gate Resistance	$R_{g(int)}$	Ω	-	1.8	-	
Switching Times	Rise Time	t_r	1.1	2.1	3.1	$V_{CC}=1,650\text{V}$, $I_C=800\text{A}$
	Turn On Time	t_{on}	1.7	2.5	3.3	$L=120\text{nH}$
	Fall Time	t_f	1.3	2.2	3.1	$R_G=5.6\Omega$ (3)
	Turn Off Time	t_{off}	2.7	4.2	5.7	$V_{GE}=\pm 15\text{V}$, $T_j=125^\circ\text{C}$
Peak Forward Voltage Drop	V_{FM}	V	2.0	2.5	3.0	$-I_C=800\text{A}$, $V_{GE}=0\text{V}$, $T_j=125^\circ\text{C}$
Reverse Recovery Time	t_{rr}	μs	0.2	0.7	1.2	$V_{CC}=1,650\text{V}$, $I_F=800\text{A}$ (4)
Peak Reverse Current	I_{RM}	A	-	1300	-	$L=120\text{nH}$, $T_j=125^\circ\text{C}$
Turn On Loss	$E_{on}(10\%)$	J/P	-	1.2	1.6	$V_{CC}=1,650\text{V}$, $I_C=800\text{A}$
Turn Off Loss	$E_{off}(10\%)$	J/P	-	1.3	1.7	$L=120\text{nH}$, $R_G=5.6\Omega$ (3)
Reverse Recovery Loss	$Err(10\%)$	J/P	-	1.0	1.5	$V_{GE}=\pm 15\text{V}$, $T_j=125^\circ\text{C}$

Notes: (3) R_G value is the test condition's value for decision of the switching times, not recommended value. Please, determine the suitable R_G value after the measurement of switching waveforms(overshoot voltage, etc.) with appliance mounted.

(4) Counter arm IGBT $V_{GE}=\pm 15\text{V}$

2) DIODE

Item	Symbol	Unit	Min.	Typ.	Max.	Test Conditions
Collector Emitter Cut-Off Current	I_{AKS}	mA	-	-	12	$V_{AK}=3,300\text{V}$, $T_j=25^\circ\text{C}$
Peak Forward Voltage Drop	V_F	V	2.2	2.7	3.2	$I_F=800\text{A}$, $T_j=125^\circ\text{C}$ At Main terminal
Reverse Recovery Time	t_{rr}	μs	0.2-	0.7	1.2	$I_F=800\text{A}$, $V_{CC}=1,650\text{V}$ (5)
Peak Reverse Current	I_{RM}	A	-	1300	-	$L=120\text{nH}$, $T_j=125^\circ\text{C}$
Reverse Recovery Loss	$Err(10\%)$	J/P	-	1.0	1.5	

Notes: (5) Counter arm IGBT $V_{GE}=\pm 15\text{V}$

- * Please contact our representatives at order.
- * For improvement, specifications are subject to change without notice.
- * For actual application, please confirm this spec sheet is the newest revision.

MBL800E33E

THERMAL CHARECTERISTICS

Item	Symbol	Unit	Min.	Typ.	Max.	Test Conditions
Thermal Impedance	IGBT	Rth(j-c)	-	-	0.013	Junction to case
	FWD	Rth(j-c)	-	-	0.026	
Contact Thermal Impedance	Rth(c-f)	-	-	0.008	-	Case to fin with thermal grease (6)

Notes: (6) Thermal grease thickness is 100µm using G747(Shin-Etsu Chemical Co.,Ltd)

DEFINITION OF TEST CIRCUIT




Fig.1 Switching test circuit




Fig.2 Definition of stray inductance

WAVEFORM DEFINITION





Fig.3 Definition of switching loss

MBL800E33E

CHARACTERISTICS CURVE


STATIC CHARACTERISTICS

TYPICAL




Collector Current vs. Collector to Emitter Voltage

TYPICAL




Collector Current vs. Collector to Emitter Voltage

TYPICAL



Forward Voltage of free-wheeling diode

TYPICAL







Forward Voltage of Chopper diode

MBL800E33E


DYNAMIC CHARACTERISTICS

DEPENDENCE OF CURRENT




MBL800E33E

PACKAGE OUTLINE DRAWING




CIRCUIT DIAGRAM



MBL800E33E

TRANSIENT THERMAL IMPEDANCE



Transient thermal impedance curve (Max value)

Material declaration

Please note the following materials are contained in the product, in order to keep characteristic and reliability level.

Material	Contained part
Lead (Pb) and its compounds	Solder

MBL800E33E

HITACHI POWER SEMICONDUCTORS

Notices

1. The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact Hitachi sales department for the latest version of this data sheets.
2. Please be sure to read "Precautions for Safe Use and Notices" in the individual brochure before use.
3. In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, life-support-related medical equipment, fuel control equipment and various kinds of safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement. Or consult Hitachi's sales department staff.
4. In no event shall Hitachi be liable for any damages that may result from an accident or any other cause during operation of the user's units according to this data sheets. Hitachi assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in this data sheets.
5. In no event shall Hitachi be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
6. No license is granted by this data sheets under any patents or other rights of any third party or Hitachi Power Semiconductor Device, Ltd.
7. This data sheets may not be reproduced or duplicated, in any form, in whole or in part, without the expressed written permission of Hitachi Power Semiconductor Device, Ltd.
8. The products (technologies) described in this data sheets are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety not are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.

-
- For inquiries relating to the products, please contact nearest overseas representatives that is located "Inquiry" portion on the top page of a home page.
-

Hitachi power semiconductor home page address <http://www.hitachi-power-semiconductor-device.co.jp/en/>